

XVD Vandal Resistant Dome with Built-in LEDs



	HR-LED	M-LED	
Horizontal Resolution	530 TV Lines	420 TV Lines	
Pick up Device	1/3" INTERLINE transfer CCD		
Total Pixels	PAL:795(H) x 596(V)	PAL:537(H) x 597(V)	
Effective Pixels	PAL:752(H) x 582(V)	PAL:500(H) x 582(V)	
Sync. system	2:1 Internal		
Scanning system	PAL :625 lines / 50 Fields		
Video Output	1.0 Vp-p / 75 ohm composite		
IR Cut Filter	Nil		
Electronic Shutter	Auto 1/50-1/100,000 sec.		
Lens	Vari Focal Lens : 3.5 mm -8 mm		Standard: 4.3mm
S/N Ratio	More than 48dB [AGC OFF]		
Min. Illumination	0.5 Lux colour/ F2.0	0.3 Lux colour/ F2.0	0.4 Lux colour/ F2.0
IR Distance	20m (28pcs IR LED)	20m (28pcs IR LED)	10m (14pcs IR LED)
IR Trigger	3.1 Lux / 3.7 Lux IR ON / OFF		2.6 Lux / 2.7 Lux IR ON / OFF
Power Supply	DC 12V		
Power Consumption	6.2W (Max)	5.9W (Max)	3.5W (Max)
Current	520mA (Max)	490mA (Max)	290mA (Max)
Dimension	82.5mm (H) x 119mm (Dia)		69mm (H) x 94mm (Dia)
Operating Temp	-10 to 50°C [14 to 122°F]		
Storage Temp	-20 to 70°C [-4 to 158 °F]		

- 1/3" Colour CCD
- 530TVL or 420TVL Resolution
- Vandal Resistant Casing
- Up to 20m Illumination with 28 LEDs
- 3.5-8mm Varifocal and 4.3mm Lens Options
- Easy P/T Adjustment