

An excellent choice for round-the-clock monitoring and surveillance, the cameras board camera provides high-quality, standard-resolution images 24 hours a day.



Features

- Day/night camera
- Resolution : 330 TVL
- 1/3" Format CCD
- 2.0 Lux @ F2.0
- 0.0 Lux with IR Leds ON
- 18 integrated IR Leds
- IR distance: 10-15m
- 3.8mm fixed lens
- Indoor/outdoor use, built to IP65
- Operates on 12VDC

General Specifications

Image Size	1/3" Format CCD Board Camera
Scanning Type	PAL Day/Night Change over
Operation Temperature	-14°F to 122°F (-10°C to +50°C)
Storage Temperature	-4°F to 140°F (-20°C to +60°C)
Power Source	12VDC
Lens Type	Fixed Aspherical with DC Drive
Focal Length	3.8mm @ F2.0
Field of View	Horizontal: 52.0° Vertical: 38.7° Diagonal: 65.6°
IR distance	10-15m

Video Specifications

Resolution	330 TV Lines
Minimum Illumination	2.0Lux@F2.0 (50 IRE Video Output)
Backlight Compensation	Yes
S/N Ratio	>48dB(AGCOFF)
AGC	Auto

Functional Specifications

Type	Mono/Colour
Format	PAL
Video Processor	Sony DSP (55.11)
Scanning Element	2:1 Interlace, H:15625Hz, V50Hz +/-1Hz
Image Picture Element	1/3" High Sensitivity Sony® CCD
Effective Picture Element	512H x 581V
Backlight Compensation	Center Area
Synchronization	Internal
Gamma Compensation	0.45
Video Output	1.0Vpp, 75 Ohm Unbalanced
White Balance	Auto
ATW Range	2700°K to 9100°K
Power Range	12VDC
Power Consumption	2.2W